
PRODUCT DATA SHEET

STONE TYPE WELSH BLUE PENNANT SANDSTONE

PRODUCT DIAMOND SAWN PAVING

DESCRIPTION

Appearance: Fine grained pennant sandstone

Blue grey in colour.

Finish: Sawn, Honed or Flamed

Geological Type: From the Rhondda Beds of the Pennant series of Carboniferous Sandstones

Quarry of Origin: Gwrhyd Quarry



APPLICATION

Commercial, Public area's and high status residential landscaping projects. Our Diamond Sawn Paving comes in a range of widths, thickness and finishes. Fine tolerances for the most demanding applications. This dense paving from the deepest quarry beds exceeds all expectations for class 6 use (HGV on regular basis) Local Authorities specify our Commercial Paving for town centre projects together with matching kerbs and setts in Sawn or Flamed finish.

SUPPLY

Pack Weight	Approximately 1300 < 1500 Kgs.
Packaging	Wooden Pallets

PHYSICAL PROPERTIES

Work Dimensions	Diamond Sawn 6 sides x random lengths 200mm < 900mm x 50mm, 63mm & 75mm thickness
Widths	Standard widths 300mm, 400mm, 450mm, 500mm, other widths are available, please contact the office for details.
Coverage	Paving is sold per square metre
Compressive strength	122 MPa min
Water Absorption	0.74%

FUTHER INFORMATION

WEATHERING

It should be appreciated that with all products weathering and site conditions can cause shade variation to appear on individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.

NOTE: As with all natural stone products the product is subject to colour variation.

GENERAL

Paving is sold in random lengths and to specific thicknesses. The surface texture can be plain sawn, honed or Flamed to give an even better slip resistant product.

CONTACT US

For sales and technical information contact Gwrhyd Specialist Stone Sales Office

Gwrhyd@specialiststone.com

Tel. 01639 830650 Fax. 01639 830930